

BUFFERS - Glass Lined, 8 bar



| | | Model | | | | | |
|--------------------------|------------------------------|--------------------|--------------------|--------------------|--------------------|---------------------|--------|
| | | BUFFER- GL200-8 | BUFFER- GL300-8 | BUFFER- GL500-8 | BUFFER- GL800-8 | BUFFER- GL1000-8 | |
| Product code | | 7716695 | 7716696 | 7716697 | 7720472 | 7720473 | |
| Water | Storage capacity | Litre | 197 | 292 | 490 | 780 | 980 |
| | Inlet connection (BSP) | Inch | 1" | 1" | 1" | 1 1/4" | 1 1/4" |
| | Outlet connection (BSP) | Inch | 1" | 1" | 1" | 1 1/2" | 1 1/2" |
| | Drain connection (BSP) | Inch | 1" | 1" | 1" | 1 1/4" | 1 1/4" |
| | Thermostat connection (BSP) | Inch | 3/4" | 3/4" | 3/4" | 3/4" | 3/4" |
| | Maximum working pressure | bar | 8 | 8 | 8 | 8 | 8 |
| | Maximum working temperature | °C | 90 | 90 | 90 | 90 | 90 |
| ErP | ErP efficiency | | B | B | C | B | C |
| | Standing loss | kWh/24h | 1.34 | 1.61 | 2.23 | 2.14 | 2.76 |
| Misc | Weight full | kg | 258 | 369 | 615 | 948 | 1168 |
| | Weight empty | kg | 61 | 77 | 125 | 168 | 198 |
| | Insulation Thickness | mm | 50 | 50 | 50 | 80 | 80 |
| Dimensions | Height of water cylinder | mm | 1205 | 1685 | 1690 | 1840 | 2250 |
| | Diameter of water cylinder | mm | 620 | 620 | 770 | 950 | 950 |
| Service clearance | Front (to allow for cathode) | mm | 500 | 500 | 500 | 500 | 500 |
| | Sides | mm | 250 | 250 | 250 | 250 | 250 |
| | Above | mm | 250 | 250 | 250 | 250 | 250 |
| Shipping | Shipping width | mm | 680 | 680 | 820 | 1000 | 1000 |
| | Shipping depth | mm | 680 | 680 | 820 | 1030 | 1030 |
| | Shipping height | mm | 1450 | 1940 | 1920 | 2040 | 2460 |
| | Shipping weight | kg | 70 | 87 | 138 | 190 | 225 |



Sales 0345 070 1055

Technical 0345 070 1057

Web andrewswaterheaters.co.uk

 [linkedin.com/company/andrews-water-heaters](https://www.linkedin.com/company/andrews-water-heaters)

 @AndrewsWH